

K SERIES TEMPERATURE CONTROL SPECIFICATIONS

	COLD CUT OUT DEG F.	WARM CUT IN DEG F.	DIFF DEG F.	RESET	CAP LENGTH	CAP TYPE	MOUNTING CENTERS (IN.)	INCLUDED COMPONENTS
K12 Thermostat All have SPST switch rated at 16A @ 120VAC. OPENS LOW, FIXED CONST CUT-IN, DIAL ADJUSTS CUT								
K12L-1560-035	29	39		SHAFT	72"	TIN	2 3/16	KNOB, PLATE, TERMINAL COVER
K12L-1549-000	21.5	40		SLOT	48"	TIN .39 X .787	2 3/16	
K12L-1561-000	23.9	37		SLOT	29.5"	TIN	2 3/16	MOUNTING SCREWS
K12L-1545-000	28.5	40		SLOT	36.4"	TIN .38 X 1.38	2 3/16	TERMINAL COVER
K12L-1533-000	28.5	40		SHAFT	35.4"	TIN .38 X 1.38	2 3/16	KNOB, PLATE, TERMINAL COVER
K12L-1535-000	26.5	36.5		SHAFT	21"	TIN .31 X 2.56	2 3/16	
K12L-1536-000	28.5	40		SHAFT	36.5"	TIN .38 X 1.38	2 3/16	TERMINAL COVER
K12L-1539-000	29	42		SLOT	36.5"	TIN .38 X 1.50	2 3/16	TERMINAL COVER
K12L-1542-000	23	38		SLOT	56"	TIN .38 X 1.50	2 3/16	TERMINAL COVER
K12L-1548-000	26	38		SLOT	39.4"	TIN	2 3/16	TERMINAL COVER
K22 Thermostat All have SPDT switch rated at 16A @ 120VAC. CONSTANT DIFFERENTIAL								
K22L-2068-000	19.4		9	SLOT	78.7"	TIN	2 3/16	DIAL PLATE
K22L-2060-000	86		5.5	SHAFT	11.8"	TIN	1 1/8	
K36 Thermostat All have SPST or SPDT switch rated at 16A @ 120VAC.								
K36L-5017-000	189		5	SLOT	35.5"	PLAIN .26 X 3.86	2 3/16	
K36L-5013-000	206.5		5	SLOT	19.7"	PLAIN .37 X 3.86	1 7/64	
K36P-1320-000	OFF		10	FIXED	21"	TIN	2 3/16	
K36L-5032-000	200		5	SLOT	35.5"	PLAIN .26 X 4.33	2 3/16	
K50 Thermostat All have SPST switch rated at 10A @ 120VAC. OPENS LOW, CONSTANT DIFFERENTIAL								
K50H-1122-000	33.5	39.2	5	SHAFT	33.5"	TIN	STUD MT	TERMINAL COVER
K50L-3065-000	-15	12.2	12	SHAFT	17.7"	TIN	STUD MT	
K50L-3142-000	38.5	50.3	6.8	SLOT	30"	TIN	2 3/16	
K50L-3226-000	52	70	6	SLOT	72.5"	TIN	2 3/16	
K50L-3260-000	28.5	52.5	8	SLOT	48"	TIN	2 3/16	
K50L-6504-000	19	65	26	SLOT	27.5"	TIN	2 3/32	
K50L-6516-000	10	54	26	SLOT	27.5"	TIN	2 3/32	
K50L-6519-000	-18	20	24	SHAFT	20"	TIN	3	
K50L-6525-000	20.5	30.5	24.5	SLOT	27.5"	TIN	STUD MT	
K50L-6529-000	-18	20	24	SHAFT	20"	TIN	3	
K50P-1125-001	34.5	51.8	4.7	SHAFT	78.7"	TIN	2 3/16	KNOB, PLATE, BRACKET

K SERIES TEMPERATURE CONTROL SPECIFICATIONS

	COLD CUT OUT DEG F.	WARM CUT IN DEG F.	DIFF DEG F.	RESET	CAP LENGTH	CAP TYPE	MOUNTING CENTERS (IN.)	INCLUDED COMPONENTS
K50P-1125-010	34.5	51.8	4.7	SHAFT	78.7"	TIN	2 3/16	KNOB
K50P-1167-000	-22	8.6	12.6	SHAFT	43.3"	TIN	STUD MT	TERMINAL COVER
K50P-1192-037	42.5	57.6	6	SLOT	35.4"	TIN	2 3/16	
K50P-1227-000	35	54	10	SLOT	30"	TIN	2 3/16	
K50P-1270-036	37	51	6	SLOT	35.4"	TIN	2 3/16	
K50P-1283-000	-4	44.6	12.6	SHAFT	98.4"	TIN	STUD MT	
K50P-1289-000	41	53	3	SLOT	35.5"	TIN	2 3/16	
K50P-1291-001	8.6	29	7	SHAFT	78.7"	TIN	STUD MT	
K50P-1299-000	32.9	46.0	6	SLOT	23.6"	TIN	2 3/16	
K50P-1336-000	6.8	39.7	19.4	SHAFT	27.6"	TIN	STUD MT	
K50P-1412-000	6	45	31	SLOT	35.4"	TIN	2 3/16	
K50P-1419-000	-22	-4	14.4	SHAFT	19.6"	TIN	2 3/16	
K50P-1429-000	32	52	6	SLOT	54"	TIN	2 3/16	
K50P-5588-000	9.6	OFF	31.5	FIXED	15.7"	TIN	2 3/16	
K50P-6062-036	6.6	48	14.5	SLOT	21"	TIN	2 3/16	
K50P-6071-000	17.5	49	25	SLOT	27.5"	TIN	2 3/16	
K50P-6075-000	5.6	48	19.5	SLOT	35.4"	TIN	2 3/16	
K50P-6120-000	-30.5	-8.3	25.2	SHAFT	43.3"	TIN	2 3/16	
K50P-6121-000	8.5	48	18	SLOT	23.6"	TIN	2 3/16	
K50P-6124-000	10	54	26.5	SLOT	27.5"	TIN	STUD MT	
K50P-6127-000	5.5	54.5	39	SLOT	15.7"	TIN	2 3/16	
K50P-6130-000	-3	45	40	SLOT	15.7"	TIN	2 3/16	
K50P-6134-000	2.5	44.8	35	SLOT	27.5"	TIN	2 3/16	

K52 Thermostat All have SPST switch rated at 10A @ 120VAC. OPENS LOW, 2 TEMP SENSORS

K52L-1010-000	23	39	7.5	SHAFT	75"	TIN	2 3/16	
K52L-1011-000	26.8	42	2	SHAFT	75"	TIN	1 7/32	

K54 Thermostat All have SPST switch rated at 10A @ 120VAC. OPENS LOW, CONSTANT DIFF, W/SIGNAL SWITCH

K54L-7514-000	-23.5	4.1	16	SHAFT	33"	TIN	1 11/16	
---------------	-------	-----	----	-------	-----	-----	---------	--

K55 Thermostat All have SPST switch rated at 16A @ 120VAC. OPENS LOW, CONSTANT DIFFERENTIAL

K55L-5041-000	41	74	5	SLOT	33.5"	TIN	2 3/16	
K55L-5057-000	26	48	19.4	SHAFT	23.5"	TIN	1 7/64	
K55L-5094-000	75	120	7	SLOT	47.2"	PLAIN	2 3/16	

K SERIES TEMPERATURE CONTROL SPECIFICATIONS

	COLD CUT OUT DEG F.	WARM CUT IN DEG F.	DIFF DEG F.	RESET	CAP LENGTH	CAP TYPE	MOUNTING CENTERS (IN.)	INCLUDED COMPONENTS
K57 Thermostat	All have SPST switch rated at 10A @ 120VAC. OPENS LOW, CONSTANT DIFFERENTIAL							
K57P-2008-000	-6.2	28.5	21	SHAFT	23.5"	TIN	2 3/16	
K59 Thermostat	All have SPST switch rated at 10A @ 120VAC. OPENS LOW, FIXED CONSTANT CUT-IN DIAL ADJ CUT-OUT, AUX ON							
K59L-1020-035	-24.0	3.0	39	SHAFT	31"	TIN	2 3/16	BRACKET, KNOB
K59P-4821-000	-9.5	12.2	38	ADAPT.	79.8"	TIN	Adjustable	BRACKET, DIAL SHAFT
K59P-4826-035	2.5	17.8	39	ADAPT.	79.8"	TIN	Adjustable	BRACKET, KNOB, SHAFT
K59P-4885-000	-1.0	16.7	30	SHAFT	15.7"	TIN	1 1/8	
K59P-4889-000	1.4	12.0	29	SHAFT	15.7"	TIN	1 1/8	
K59P-4898-000	5.0	12.0	28.9	SHAFT	24"	TIN	1 1/8	
K60 Thermostat	All have SPST switch rated at 10A @ 120VAC. OPENS LOW, CONSTANT DIFFERENTIAL, PUSH TO DEFROST							
K60P-1042-000	-6.7	44	14	SHAFT	23.5"	TIN .34 X 2.4	13/16	KNOB
K61 Thermostat	All have SPST switch rated at 10A @ 120VAC. OPENS LOW, FIXED CONSTANT CUT-IN DIAL ADJ CUT-OUT, AUX ON							
K61L-1501-000	-0.4	17.6	38	SHAFT	70.9"	TIN	STUD MT	KNOB