


Thermopiles

TP-75 & CP-2 1950 & 1951 Series

Robertshaw
RANCO • PARAGON • CASTFUTURA



Description

Robertshaw® thermopiles are the industry leader for gas appliance applications. Their primary function is to ensure a standing pilot light is operative so that on a call for heat, the main burner gas will be properly ignited. Thermopiles are placed in gas applications to detect the existence of a flame for safety purposes by shutting off the potential gas flow to a burner. A thermopile is the assembly of many thermocouples to increase the millivolt output. Robertshaw thermopiles have two types of connections: coaxial and two-wire spade connectors. The 1950 thermopiles, also known as TP-75, are two-wire spade connectors. The 1951 thermopiles, also known as CP-2 (500-600 millivolts) are coaxial connectors. The 1950 and 1951 Series Thermopiles (pilot generators) are designed for use on self-powered gas control systems. They can be used to replace similar competitive devices.

Features and Benefits

- Easy burner installation with attached threaded nut
- Stainless steel outer jacket for long life and resistance to heat blistering
- Combination of copper and nickel alloys for good electrical conductivity
- Mica washer to insulate from shorting conditions
- Various lengths available for multiple applications

Specifications

- Lead lengths range from 18 to 60" (460 to 1525 mm)
- Open circuit output: 500-750 millivolts
- Connection Type: Male connector nut
- Includes PG9 Pilot Adaptor

3 Year
Limited
Warranty




Customer Service
+1 800 304 6563
HVACCustomerService
@robertshaw.com

Technical Service
+1 800 445 8299
TechnicalService
@robertshaw.com


www.robertshaw.com
©2024 Robertshaw
11/25 150-2379 Rev C

Product Dimensions

TP-75 Series



CP-2 Series



Available in the following lengths:

Overall "X" Length

- 12" [304,8]
- 15" [381,0]
- 18" [457,2]
- 19" [482,6]
- 20" [508,0]
- 21" [533,4]
- 24" [609,6]
- 26" [660,4]
- 30" [762,0]
- 36" [914,4]
- 40" [1016,0]
- 42" [1066,8]
- 48" [1219,2]
- 54" [1371,6]
- 60" [1524,0]
- 72" [1828,8]

