



RSG-2S

RSG-4S

Description

The Ranco® Sight Glasses are installed after the filter drier in the liquid line of refrigerating systems. Typically, in a system with an expansion valve, a sight glass is usually fitted in the liquid line immediately after the filter drier. Sight glasses are typically used in refrigeration systems in order to observe the property changes of the refrigerant (liquid/vapor) itself, but also to indicate whether the moisture content of the refrigerant is within an acceptable range. The sight glass also indicates whether liquid refrigerant is present at the expansion component. If the moisture content is within the acceptable range, the indicator color is green and no further action is necessary. If the indicator is yellow, there is a problem with the moisture content of the refrigerant. Excessive moisture content can cause icing of the expansion valve if the evaporating temperature is below freezing. In addition, excessive moisture in the system reacts with the oil normally used in modern refrigeration systems (polyester oil) to form acids. Another phenomenon of Frothing in the sight glass indicates either a shortage of refrigerant or that the refrigerant in the liquid line is not entirely in the liquid state.

Features and Benefits

- Pure copper solder connections
- Precise color indicator for rapid identification of moisture issues
- Clear indicator visibility
- Leak free performance (PTFE seals)
- Corrosion resistant brass housing

Applications

- Systems with expansion components
- Used in tandem with filter driers

1 Year
Limited
Warranty



Robertshaw
RANCO • PARAGON • CASTFUTURA

Customer Service
+1 800 304 6563
HVACCustomerService
@robertshaw.com

Technical Service
+1 800 445 8299
TechnicalService
@robertshaw.com

www.robertshaw.com
©2025 Robertshaw
05/25 150-2771 RevD

Specifications and Replacement Information

Part Numbers	Description	Fitting In	Fitting Out	Emerson	Parker Hannifin	Replaces		
						Danfoss	Sanhua	Sporlan
RSG-2S	1/4" ODF Solder x ODF Solder Moisture Indicator	1/4" ODF	1/4" ODF	HMI-1TT2	PSG-2S	SGP 6SN	SG-2-S	SA-12S
RSG-3S	3/8" ODF Solder Sight Glass	3/8" ODF	3/8" ODF	HMI-1TT3	PSG-3S	SGP 10SN	SG-3-S	SA-13S
RSG-4S	1/2" ODF Solder Moisture/Liquid Indicator	1/2" ODF	1/2" ODF	HMI-1TT4	PSG-4S	SGP 12SN	SG-4-S	SA-14S
RSG-5S	5/8" ODF Solder Moisture/Liquid Indicator	5/8" ODF	5/8" ODF	HMI-1TT5	PSG-5S	SGP 16SN	SG-5-S	SA-15S
RSG-7S	7/8" ODF Solder Moisture/Liquid Indicator	7/8" ODF	7/8" ODF	HMI-1TT7	PSG-5S	SGP 22SN	SG-7-S	SA-17S
RSG-2FM	1/4" Female x Male Flare Moisture/Liquid Indicator	1/4" FF	1/4" MF	AMI-1FM2	PSG-2MF	SGP 6N	SG-2-FM	SA-12FM
RSG-3FM	3/8" FFL x MFL Moisture Indicator	3/8" FF	3/8" MF	AMI-1FM3	PSG-3MF	SGP 10N	SG-3-FM	SA-13FM
RSG-4FM	1/2" FFL x MFL Moisture Indicator	1/2" FF	1/2" MF	AMI-1FM4	PSG-4MF	SGP 12N	SG-4-FM	SA-14FM